

Safety Vault

High Security



Operating Environment

Voltage: 100V-240V AC, 50/60Hz
Temperature: 0°C to 40°C
Humidity: 20% to 95% noncondensing



Functionality

Third Party or Self cash deposit
Bulk Cash Acceptor
Cash Deposit
Real time cash deposit



Features

Reliable performance
Compact footprint
High-speed and large capacity
Dustproof/waterproof construction
High security and cost-effective



INTEGRATION

The machine could be integrated into any Bank database e.g. T24 provided that approved APIs are given.



Bulk Cash Depository Machine



CONTACTS



Manufacturer:

TopGood Intelligent Technology Co., Ltd
Email: sales@sztopgood.com
Phone: +86 755 29420029

Authorised Dealer:

ASSOCIATECH ELECTRICAL LIMITED
Email: info@associatechelectrical.com
Phone: +265 999 337 898



WITH ONE YEAR WARRANTY

1 YEAR WARRANTY

KL 174 BULK CASH DEPOSITORY MACHINE

Handling and making cash deposits is already a tedious task. Our Bulk Cash Depository Machine is designed to alleviate this, by achieving the ultimate merger of self-service and in-branch convenience.

Waiting in queues for simple tasks such as depositing cash, can be cumbersome and better spent elsewhere. The Topgood KL 174 heavy duty deposit taking machine accepts deposits in bulk, reduces time spent queuing and enhances the deliverability of services offered.



SPECIFICATIONS

User-interface

17inch TFT LCD display
Capacitive touch screen
EPP keypad be compliant with PCI, vandal resistance
Loudspeakers



Card reader (Optional)

Motorized hybrid or dip card reader EMV certified Support magnetic card, IC card, RF card retracted if not removed



Control Unit

Industrial control computer
Core i5 Series CPU, 3.2G,
RAM 8G, SSD 128G
Operating system: Win 10



Printer

80mm thermal graphic printer
Speed > of 150 mm/sec;
Alarm & sensor: near end, jam, black mark



Electronic Lock

High security lock



Cash bag Guarding Sensor

High sensitivity sensor



Maintenance Screen

17inch P-cap open frame touch monitor
Brighttiness: 250cd/m2



Communication

Standard TCP/IP
Optional: Wireless, 4G



Bundle Cash acceptor

Accept: 600notes,
Reject: 50 notes,
Escrow: 100 notes.
Support banknotes size:
width 100-180mm length: 50-90mm
thickness: 0.05-0.12mm



Cash Acceptor Counting Speed:

Default Speed: 1000 notes/minute
Optional Speed:
800 notes/minute
600 notes/minute



Counterfeiting Methods:

UV/MG/MT/IR
Jam rate: less than 0.5%
Mistaken reject rate: less than 2%



Cash Bag Capacity:

30,000 notes.
Customized Cash Bag Capacity



Security

Dial combination lock mechanism
Fraudulent device inhibitor (FDI)
EPP shield
Built-in cameras



Keypad (Optional)

KMY3501B-PCL,
Supprts: DES/3DES applying
ECB/CBC encryption

